

# Datasheet Conveyor Belt



## NITTA CORPORATION OF HOLLAND

Berenkoog 25  
1822 BH Alkmaar  
The Netherlands

T: +31 (0)72 562 22 34  
F: +31 (0)72 561 32 38

E: sales@nitta.nl  
www.nittacorporation.com

- **NITTA BELT TYPE:**  
**1 NFP 02/W2**
- **Nitta Japan code:**



**Construction:** 1 ply polyester, non-rigid

	TOP COVER	INNER LAYER	BOTTOM SIDE	
<b>Material:</b>	PU	-	Fabric	
<b>Thickness:</b>	0,2			mm (approx.)
<b>Colour:</b>	White	Not applicable		
<b>Hardness:</b>	87 Shore A			
<b>Profile:</b>	-			

**Total thickness:** 0,9 mm (approx.)  
**Weight:** 1 kg/m<sup>2</sup> (approx.)  
**Max. width:** 3000 mm  
**Belt support:** Sliderbed (Rollers), Flat/trough

**Rating at 1% elongation:** 9 N/mm  
**Advised pretension:** 2 - 4 N/mm  
**Maximum allowable tension:** 10 N/mm  
**Temperature range:** -20 to +80 °C

**Minimum pulley diameters:**  
**Flexing:** 10 mm  
**Backflexing:** 15 mm

**Special approval:** FDA, 10/2011/EC + amendments

**Applications:** Light duty conveyor belt in the food industry  
 Curved conveyors  
 Oil and grease resistant

Date of issue 20-10-2014-1

Your Partner In Belting Solutions

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nittacorporation.com